






High Pressure Cleaner

HDE840 24kW



	1400 U/min	TSS
TOTAL STOP		
		

Type	HDE840 24kW-Standard		HDE840 24kW-Premium		
Voltage	3/N/PE/AC/50Hz/400V	<ul style="list-style-type: none"> Etronic I - Controls 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve 	<ul style="list-style-type: none"> Etronic I - Controls Hose-Reel 20m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve 		
Operating pressure	30-140bar/3-14MPa				
Max. pressure	160bar/16MPa				
Discharge capacity	300-720l/h				
Nozzle size	045				
Heating capacity	24kW				
Hot water capacity	30-80°C				
Pump speed	1400rpm				
Connected load	28,8kW/44A				
Electrical protection	3x50A slow				
Weight net/with package		124kg/145kg		133kg/154kg	
Dimensions device/with package (LxWxH)		107x73,5x102cm/119x88x127cm		107x73,5x102cm/119x88x127cm	

Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of ABS, stainless-steel hotwater-boiler with 65l capacity with pre-heating and buffer storage for immediate hot-water use and hot-water preparation during stand-by operation, triplex-piston pump with chrome nickel pump head (hot-water resistant), high-performance ceramic piston, stainless-steel valves,leakage-return, Etronic I - controls: (start-stop system with switch-off delay, stand-by system for heating, low-water cut-off), unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, 2 integrated detergent-tank with 20l capacity, 2-stage rotary on-off switch with stand-by function, 7,5m connection cable, removable ergonomic drawbar.

Art.No.	108001	108002
----------------	--------	--------