







# High Pressure Cleaner

**KD823**



	<b>1400 U/min</b>	<b>TSS</b>
<b>TOTAL STOP</b>		
		

Type	KD823-Standard		KD823-Premium
Voltage	1/N/PE/AC/50Hz/230V	<ul style="list-style-type: none"> <li>10m HP-Hose DN06 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>17l Cleaning-Detergent tank</li> <li>Detergent-Supply c/w Low-Pressure Injector and Metering-valve</li> </ul>	<ul style="list-style-type: none"> <li>Hose-Reel</li> <li>15m HP-Hose DN06 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>15l Water-Storage tank</li> <li>Water-Supply separation acc. DIN EN 1717 class 4</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Operating pressure	30-140bar/3-14MPa		
Max. pressure	160bar/160MPa		
Discharge capacity	300-720l/h		
Nozzle size	045		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	3,2kW/14,7A		
Electrical protection	16A slow		
Weight net/with package		49kg/72kg	55kg/78kg
Dimensions device/with package (LxWxH)		80,5x48,5x95cm/109x63x104cm	80,5x48,5x95cm/109x63x104cm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar.

<b>Art.No.</b>	562001	562002
<b>Retail price plus VAT</b>	1.699,00€	2.019,00€